

	l Data

Technical Data	
Power range	2600 W
Drilling range	
Power source type	Electric
Rated voltage	110 V
Rated current	22.5 A
Dimensions (LxWxH)	
Weight in accordance with EPTA-Procedure 01/2003	12.7 kg
Weight complete	30 kg
Water collection system	Yes
Operating Range without laser receiver	
Speed 1 (no load)	320 rpm
Speed 2 (no load)	640 rpm
Speed 3 (no load)	1300 rpm
Coring range gear 1 (dry)	
Coring range gear 1 (wet)	152 mm - 400 mm
Coring range gear 2 (dry)	
Coring range gear 2 (wet)	82 mm - 162 mm
Coring range gear 3 (dry)	
Coring range gear 3 (wet)	25 mm - 82 mm
Coring range gear 4 (dry)	
Coring range gear 4 (wet)	
Coring range gear 5 (dry)	
Coring range gear 5 (wet)	
Coring range gear 6 (dry)	
Coring range gear 6 (wet)	
Coring range gear 7 (dry)	
Coring range gear 7 (wet)	
Coring range gear 8 (dry)	
Coring range gear 8 (wet)	
Coring range gear 9 (dry)	
Coring range gear 9 (wet)	
Coring range gear 10 (dry)	
Coring range gear 10 (wet)	
Drilling range - dry	
Drilling range - wet hand held	
Drilling range - wet w/ stand	25 mm - 400 mm
Opt. drilling range	
Opt. drilling range - dry	
Opt. drilling range - wet hand held	
Opt. drilling range - wet w/ stand	
Package content	DD 200 unit with BL chuck