

S1VR- MS3VR - 1UFTVR U3VR - U5VR - CCVR

1UFTVR

For surface preparation of small areas or areas close to walls or between re-bars, the 1UF-TVR is second to none. Its also the ideal tool to compliment the U3-VR or the FB5-VR to scabbler edges where larger Machines cant reach. It can remove up to 4 square metres per hour x 4mm deep, to a depth of 50mm. The vibration levels transmitted to the operator by the are typically less than 10% of the levels which are transmitted by the "Standard" 1UF pole scabbler.

	HEADS	HEADS WEIGHT		WRKING WIDTH	AIR CONS	REC.WRKG	HOSE FITTING	
model	qty	lbs kg	ins mm	ins mm	cfm L/sec	psi bar		
1UFTVR	1	36 16.5	52 1320	3 75	25 12	90 6	3/4"	



U3VR

Vibration Reduced Pneumatic Scabbling Tools are specifically designed for all types of surface work on concrete where it is necessary to carry out surface hammering without in any way damaging the basic concrete.

	HEADS	WEIGHT	LENGTH	WIDTH	HEIGHT	WRKING WIDTH	AIR CONS	REC.WRKG	HOSE FITTING
model	qty	lbs kg	ins mm	ins mm	ins mm	ins mm	cfm L/sec	psi bar	
U3VR	3	125 57	50 1270	25 635	33 838	5.5/8 143	100 48	90 6	3/4.BSP

