

Main specifications	
Single-phase maximum power (LTP)	n.a.
Single-phase maximum power (LTP)	n.a.
Single-phase prime power (PRP)	n.a.
Single-phase prime power (PRP)	n.a.
Single-phase continuous power (COP)	n.a.
Single-phase continuous power (COP)	n.a.
Rated maximum power (LTP)	2,87 kVA
Rated maximum power (LTP)	2,6 kW
Rated prime power (PRP)	2,64 kVA
Rated prime power (PRP)	2,4 kW
Rated continuous power (COP)	2,4 kVA
Rated continuous power (COP)	2,2 kW
Rated current at COP	10,4 A
Phases	1
Voltage	230 V
Rated power factor	0,9 PF
Frequency	50 Hz
Battery charger voltage	n.a.
Battery charger current	n.a.
Panel location	On alternator
Frame type	Tubular
Compliancy certification	CE
Engine specifications	
Engine manufacturer	Honda
Model	GX160
Stroke	4
Fuel	Gasoline
Number of cylinders and disposition	1, inclination angle
Displacement	163 cm ³
Air intake	Natural
Starting system	Recoil
Nominal operating speed	3000 rpm
Speed governor	Mechanical
Continuous power COP	2,5 kW
Prime power PRP	2,8 kW
Standby power LTP	3,2 kW
Lube oil capacity	0,6 l
Fuel consumption at 75% load	0,93 l/h
Electric circuit voltage	n.a.
Alternator specifications	
Alternator manufacturer	MeccAlte
Model	S15W 85/A
Poles	2
Revolution speed	3000 rpm
Voltage	230 V
Frequency	50 Hz
Efficiency at 75% load	71,8 %
Maximum admitted overload	10% for 1 hour every 6 hours of running time S2
Voltage regulation system	Capacitor
Protection grade	IP 23
Additional information	
Skid mounting	No
Fuel tank location	On engine
Fuel tank capacity	3,6 l
Automatic supplementary tank VV.FF.	No
Running time at 75% COP	3,86 h
Measured acoustic power (LWA) at 4 mt	93,2 dBA
Noise level at 7 m	68,2 dBA
Guaranteed noise level (LWA)	94 dBA
Operating conditions	-15 ~ +40 °C
Dimensional data	
Length	625 mm
Width	455 mm
Height	455 mm
Dry weight	37 kg